

ZY 系列 ACDC 开关电源 120W-420W

产品特点

- ◆ 输入电压范围 85-264VAC/120-370VDC
- ◆ 输入频率 47-63HZ, 主动式 PFC+同步整流
- ◆ 输出短路、过压、过流、过温保护
- ◆ 功率因数 0.95-0.99 (230VAC-115VAC)
- ◆ 电压精度, 全负载范围±1%
- ◆ 线性调整率, 额定负载±0.5%
- ◆ 负载调整率, 0%-100%负载±0.5%
- ◆ 纹波噪声 20MHz 带宽, 峰-峰值 0.5%
- ◆ 工作温度-10℃-+50℃, 储存温度-40℃-+85℃
- ◆ 工作湿度 20-90%RH, 储存湿度无冷凝 10-95%RH
- ◆ 漏电流, 240VAC<0.1mA,基板涂覆三防漆
- ◆ 隔离电压, 输入-输出 4000VAC/1min,输入-地 1500VAC/1min,输出-地 1500VAC/1min

产品型号	冷却方式	输出功率	输出电压电流	效率	外形尺寸
ZY120S12	自然风冷	120W	12V/10A	93%	76*50*35mm
	13CFM 风扇	150W	12V/12A	93%	76*50*35mm
ZY120S24	自然风冷	120W	24V/5A	93%	76*50*35mm
	13CFM 风扇	150W	24V/6A	93%	76*50*35mm
ZY120S36	自然风冷	120W	36V/3.3A	93%	76*50*35mm
	13CFM 风扇	150W	36V/4A	93%	76*50*35mm
ZY120S48	自然风冷	120W	48V/2.5A	93%	76*50*35mm
	13CFM 风扇	150W	48V/3A	93%	76*50*35mm
ZY120S110	自然风冷	120W	110V/1.1A	93%	76*50*35mm
	13CFM 风冷	150W	110V/1.4A	93%	76*50*35mm
ZY150S12	自然风冷	150W	12V/12.5A	93%	102X52X30mm
	13CFM 风扇	220W	12V/18.7A	93%	102X52X30mm
ZY150S28	自然风冷	150W	28V/5.35A	93%	102X52X30mm
	13CFM 风扇	220W	28V/7.85A	93%	102X52X30mm
ZY150S36	自然风冷	150W	36V/4.17A	93%	102X52X30mm
	13CFM 风扇	220W	36V/6.2A	93%	102X52X30mm
ZY150S48	自然风冷	150W	48V/3.13A	93%	102X52X30mm
	13CFM 风扇	220W	48V/4.6A	93%	102X52X30mm
ZY150S110	自然风冷	150W	110V/1.4A	93%	102X52X30mm
	13CFM 风扇	220W	110V/2A	93%	102X52X30mm
ZY250S12	自然风冷	250W	12V/20.8A	93%	124X60X35mm
	20.5CFM 风扇	320W	12V/26.6A	93%	124X60X35mm
ZY250S28	自然风冷	250W	28V/8.9A	93%	124X60X35mm
	20.5CFM 风扇	320W	28V/11.4A	93%	124X60X35mm
ZY250S36	自然风冷	250W	36V/6.9A	93%	124X60X35mm
	20.5CFM 风扇	320W	36V/8.9A	93%	124X60X35mm

产品型号	冷却方式	输出功率	输出电压电流	效率	外形尺寸
ZY250S48	自然风冷	250W	48V/5.2A	93%	124X60X35mm
	20.5CFM 风扇	320W	48V/6.7A	93%	124X60X35mm
ZY250S110	自然风冷	250W	110V/2.3A	93%	124X60X35mm
	20.5CFM 风扇	320W	110V/2.9A	93%	124X60X35mm
ZY350S12	自然风冷	350W	12V/29A	93%	127X76X36mm
	25CFM 风扇	420W	12V/35A	93%	127X76X36mm
ZY350S24	自然风冷	350W	24V/14.6A	93%	127X76X36mm
	25CFM 风扇	420W	24V/17.5A	93%	127X76X36mm
ZY350S36	自然风冷	350W	36V/9.7A	93%	127X76X36mm
	25CFM 风扇	420W	36V/11.7A	93%	127X76X36mm
ZY350S48	自然风冷	350W	48V/7.3A	93%	127X76X36mm
	25CFM 风扇	420W	48V/8.8A	93%	127X76X36mm
ZY350S110	自然风冷	350W	110V/3.2A	93%	127X76X36mm
	25CFM 风扇	420W	110V/3.8A	93%	127X76X36mm

*列表中冷却方式为风扇的指用户使用时外加

*本表额定功率测试条件为常温 25℃

*特殊规格的输出电压及特殊要求可以定制

